

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

UnshieldedAudio, Control and Instrumentation Cables
Non-PlenumJameco Part Number 234055
(8443-060-U1000)

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

22 AWG Solid Conductors • Bare Copper • Conductors Cabled

Polyethylene Insulation • Rose Gray PVC Jacket														
 UL AWM Style 2092 (300V 60°C)	8795	NEC:	2	Red, Green	U-500	U-152.4	10.0	4.5	.018	.46	.022	.56	.168	4.27
		CM			U-1000	U-304.8	19.0	8.6						
		CEC: CM			1000	304.8	21.0	9.5						
 UL AWM Style 2093 (300V 60°C)	8794	NEC:	3	Green, Red, Yellow	U-1000	U-304.8	22.0	10.0	.018	.46	.022	.56	.178	4.52
		CM			1000	304.8	23.0	10.5						
 UL AWM Style 2094 (300V 60°C)	9794	NEC:	4	Green, Red, Yellow, Black	U-500	U-152.4	14.0	6.4	.018	.46	.025	.64	.200	5.08
		MP, CM			U-1000	U-304.8	27.0	12.3						
					1000	304.8	27.0	12.3						

22 AWG Stranded Conductors (7x30) • Tinned Copper • Conductors Cabled

PVC Insulation • Chrome PVC Jacket														
	8442	NEC:	2	Black, Red	100	30.5	2.4	1.1	.015	.38	.025	.64	.170	4.32
		CMG			U-500	U-152.4	7.5	3.4						
		CEC:			500	152.4	7.5	3.4						
		CMG FT4			U-1000	U-304.8	15.0	6.8						
					1000	304.8	15.0	6.8						
				10000	3048.0	150.0	68.2							
UL AWM Style 2576 (150V 80°C) 	8443	NEC:	3	Black, Red, Green	100	30.5	2.8	1.3	.010	.25	.032	.81	.172	4.37
		CMG			U-500	U-152.4	9.5	4.3						
		CEC:			500	152.4	9.5	4.3						
		CMG FT4			U-1000	U-304.8	18.0	8.2						
					1000	304.8	18.0	8.2						
	8444	NEC:	4	See Chart 1 (Tech Info Section)	100	30.5	3.2	1.5	.010	.25	.032	.81	.185	4.70
		CMG			U-500	U-152.4	11.5	5.2						
		CEC:			500	152.4	11.5	5.2						
		CMG FT4			U-1000	U-304.8	22.0	10.0						
					1000	304.8	23.0	10.5						
	8445	NEC:	5	See Chart 1 (Tech Info Section)	100	30.5	3.5	1.6	.010	.25	.032	.81	.194	4.93
		CMG			U-500	U-152.4	13.5	6.1						
		CEC:			500	152.4	13.5	6.1						
		CMG FT4			U-1000	U-304.8	26.0	11.8						
					1000	304.8	26.0	11.8						
	9430	NEC:	7	See Chart 1 (Tech Info Section)	U-500	U-152.4	16.5	7.5	.010	.25	.032	.81	.214	5.44
		CMG			500	152.4	17.0	7.7						
		CEC:			U-1000	U-304.8	33.0	15.0						
		CMG FT4			1000	304.8	33.0	15.0						
	9421	NEC:	8	See Chart 1 (Tech Info Section)	100	30.5	4.7	2.1	.010	.25	.032	.81	.229	5.82
		CMG			U-500	U-152.4	18.5	8.4						
		CEC:			500	152.4	19.0	8.6						
		CMG FT4			U-1000	U-304.8	37.0	16.8						
		1000	304.8	37.0	16.8									
	9423	NEC:	9	See Chart 1 (Tech Info Section)	100	30.5	5.2	2.4	.010	.25	.032	.81	.244	6.20
		CMG			U-500	U-152.4	21.5	9.8						
		CEC:			500	152.4	21.5	9.8						
		CMG FT4			U-1000	U-304.8	42.0	19.1						
		1000	304.8	42.0	19.1									
8456	NEC:	10	See Chart 1 (Tech Info Section)	100	30.5	5.7	2.6	.010	.25	.032	.81	.264	6.71	
	CMG			U-500	U-152.4	22.5	10.2							
	CEC:			500	152.4	23.0	10.5							
	CMG FT4			U-1000	U-304.8	45.0	20.5							
				1000	304.8	46.0	20.9							

